Simply the strongest tanks on the market

> RESIDENTIAL 2-IN-1 DOUBLE-WALL OIL TANKS









2-IN-1 DOUBLE-WALL OIL TANKS | UL / ULC-2258

HDPE plastic tanks inside a galvanized secondary containment

	PRODUCT #	TOP OPENING QUANTITY	BURNER OIL SUPPLY OPENING SIZE / LOCATION	CAPACITY	DIMENSIONS		WEIGHT	Approved usage	
				US gallon	Н	W	L	lbs	Approveu usage
	961225	4	3/8" and 1/2" / Top duplex bushing	190	48"	28"	44"	150	Indoor / Outdoor*
	961226	4	3/8" and 1/2" / Top duplex bushing	265	64"	28"	44"	185	Indoor / Outdoor*

*Rain cover mandatory for outdoor installation





GENERAL CHARACTERISTICS 2-IN-1 DOUBLE-WALL OIL TANKS

- Primary tank made of blow-molded high-density polyethylene (HDPE)
- Internal tank is fluorination treated for odor and chemical resistance, which is unique to the Granby 2-in-1 tanks
- Secondary containment made of galvanized steel on both sides, tightly welded and edged using state-of-the-art manufacturing equipment
- Visual leak indicator for the monitoring of the integrity of the primary tank
- Connection fittings made of cast aluminum for greater torque resistance and greater peripheral sealing
- Rugged floor stand made entirely of galvanized steel - Suited for basements with headrooms as low as 60"
 - Ease in maneuverability and access through narrow doorways only 28" wide
- Easy carrying due to light weight and welded handles
- Optional rain cover available
- For above ground storage of #2 fuel, motor oil (new & used), 100% biodiesel and biodiesel blends up to B100

TANKS COME FULLY PACKAGED AND EQUIPPED FROM FACTORY WITH NECESSARY INSTALLATION ACCESSORIES

- 2" NPT galvanized steel fill pipe adaptor
- Vent alarm
- Overfill protection alarm
- Oil level gauge
- Oil burner supply duplex bushing with tube adaptors



2-IN-1 SAFETY TANK SYSTEM OPTIONAL AND/OR SPARE ACCESSORIES

MODEL #	DESCRIPTION				
960000	Rain cover – mandatory for outdoor installations				
962245	Installation tie-down kit for 190 USG				
962246	Tie-down kit for 265 USG				
962247	Leak indicator assembly for 190 USG				
962248	Leak indicator assembly for 265 USG				
962266	Sealed fuel oil rope gauge 190 USG				
962267	Sealed fuel oil rope gauge 265 USG				
962280	Aluminium cap nut				
971040	2" transition fiting for gauge				

MODEL #	DESCRIPTION				
E206-0001	Compression fitting 1/2" NPT x 1/2" tube				
E207F-999S	Duplex bushing with 3/8" tube fittings				
E208F-999S	Duplex bushing with 1/2" tube fittings				
E209-0001	Compression fitting 1/2" NPT x 3/8" tube				
E250-999S	Threaded 2" NPT fill pipe adaptor				
E540-999 2" NPT vent and overfill alarm					
JE03002	Gauge gasket 3.275 x 2.725 x 0.125 UL157				
JE15020	Metallic cap nut O-ring seal EPDM				

*Consult warranty documents for details.



