



A CSW Industrials Company

PRODUCT DATA SHEET

ODORGON™ Powder
Fuel Oil Absorber

Description

Odorgon Powder eliminates oil odors and absorbs oil stains from concrete and other floors. It leaves a pleasant odor after absorbing oil from spills and leaks. Sifter top can allows for controlled economical usage and clean storage.

Applications

Odorgon Powder is used to deodorize and absorb oil from leaking or overfilled tanks, oil burner drippings, in warm air vents, air filters, in garages, grease pits and on equipment.

Directions for Use

READ ALL DIRECTIONS, SDS AND LABEL BEFORE USING

Scatter powder as required over oil residue. Sweep up when odor and residue have been absorbed. For stains, scatter additional powder and sweep up when stain has disappeared. If odor source is hard to reach or inaccessible while using powder or if odor still persists, use Odorgon Spray (RectorSeal product code 68516).

For additional technical information, call Toll Free 1-800-231-3345



Characteristics | Features

- Eliminates odor
- Non-lingering, pleasant odor
- Non-Flammable
- Absorbs & deodorizes spills & leaks

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Ft per Case
68512	1 lb. (.45 kg)	12	14	0.592
68514	2 lbs. (.90 kg)	12	28	1.12

Specifications

Wt/Gal @ 77°F	N/A
Flash Point SETA CC	None
Color	Off White to Yellow
Shelf Life	2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.



DANGER!

Causes serious eye irritation.

May be harmful if inhaled.

May cause respiratory irritation.

Causes damage to organs (lung/respiratory system) through prolonged or repeated exposure (inhalation).

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300.

Contains: Earth 8031-18-3, Diatomaceous Earth 7631-86-9, Silicon Dioxide 7631-86-9. **Precautionary Statements - PREVENTION:** Avoid breathing dust/fume/gas/mist/vapors/spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear eye protection/face protection. **RESPONSE: IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **IF EXPOSED OR CONCERNED:** Get medical advice. Get medical advice/attention if you feel unwell. If eye irritation persists: Get medical advice/attention. **STORAGE:** Store in a well-ventilated place. Keep container tightly closed. Store locked up. **DISPOSAL:** Dispose of contents/container to an approved waste disposal plant.

KEEP OUT OF REACH OF CHILDREN.

For additional information, refer to Safety Data Sheet, or Call Toll Free 1-800-231-3345.

Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

PO Box 5092 • Hoppers Crossing, VIC 3029, Australia • 07-3267-7277 • rectorseal.com.au