



A CSW Industrials Company

PRODUCT DATA SHEET

ODORGON™ Spray

Fuel Oil Neutralizer

Description

Odorgon Spray is used to eliminate fuel oil odors from leaking or overfilled tanks, oil burner drippings, in warm air vents and air filters, in garages, grease pits and on equipment. The spray covers vertical surfaces as well as hard-to-get corners. Spray into return air ducts to eliminate circulating odors.

Applications

Odorgon Spray is used to deodorize and absorb oil from leaking or overfilled tanks, oil burner drippings, in warm air vents, air filters, in garages, grease pits and on equipment. It may be sprayed into return air ducts to eliminate circulating odors.



Directions for Use

READ ALL DIRECTIONS, SDS AND LABEL BEFORE USING

Spray over oil covered surface. If source of odor is not obvious, spray around general area of odor. For oil odor carried into warm air system ducts, spray Odorgon into return air duct for circulation throughout the duct work. Mild fragrance does not linger. To absorb oil residue odor and stains, use Odorgon Powder.

DANGER: Do not use chemical soot removers in furnaces with plugged, leaky or broken flues or stacks through which sparks can escape. Do not attempt to ignite soot saturated with heating oil. Such soot may flare up and cause an explosion.

Characteristics | Features

- Eliminates odor
- Non-lingering, pleasant odor
- Non-Flammable
- Absorbs & deodorizes spills & leaks

For additional technical information, call Toll Free 1-800-231-3345

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Ft per Case
68516	14 oz. (.39 kg)	12	14	0.45

Specifications

Wt/Gal @ 77°F	8.17
Flash Point SETA CC	Negative Flame , (NFPA) Level 1 Aerosol
Color	Clear
Shelf Life	2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.



Precautionary Statements

Refer to Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

For additional Technical Information Call Toll Free 1-800-231-3345



This product can expose you to chemicals including Methyl Isobutyl Ketone (MIBK), which is known to the State of California to cause cancer, birth defects or reproductive harm. For more information, go to www.P65Warnings.ca.gov.

Limited Warranty



For more information on our product limited warranty, visit RectorSeal.com

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

PO Box 5266 • Brendale, QLD 4500 Australia • 1300 772 878 • rectorseal.com.au

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2020 RectorSeal. All rights reserved. R50490-0422